



15" (14.0" VIS) XSD™ monitor

Product description

- 15-inch (14.0" VIS) color monitor with excellent front of screen performance for use with MACs and PCs
- Autoscan covers horizontal frequencies up to 63 kHz offering a maximum resolution of 1280 x 960 with flicker free display of 800 x 600 at up to 101 Hz
- Flat Square CRT with 0.28 mm dot pitch (0.24 hdp)
- XSD - Xtra Space Design™ saves desk space: World's shortest 15-inch conventional monitor with maximum depth of only 379 mm / 14.9"
- Multimedia Base and USB Hub option
- MPRII, NUTEK, EPA, FCC, CE, ISO9241 and ISO14001 certified

Optional Multimedia base 6G3B11



Optional USB HUB PCUH411



Let's make things better.



PHILIPS

15" (14.0" VIS) XSD™ monitor



Technical Specifications

CRT

- Size (inch/cm) 15"/ 36 cm
- Deflection angle (degrees) 90°
- Dot pitch 0.28 mm
- Horizontal pitch 0.24 mm
- Tube type Shadow mask, Flat Square, Anti Glare, Anti Static, Light Transmission 57%
- Phosphor P22
- Recom. display area(mm) 270 x 202 mm
- Recom. display area(inch) 10.6" x 8.0"
- Max. display area(mm) 284 x 213 mm
- Max. display area(inch) 11.2" x 8.4"

Scanning

- Horizontal scanning 30 - 63 kHz
- Vertical scanning 50 - 120 Hz

Video

- Video dot rate 108 MHz
- Input impedance -Video 75 Ohm
- -Sync 2.2k Ohm
- Input signal levels 0.7 Vpp
- Sync input signal Separate sync
- Sync polarities Composite sync
- Sync polarities Positive and negative

White color temperature

Chromaticity CIE coordinates:

- at 9300 K: x=0.283, y=0.297
- at 6500 K: x=0.313, y=0.329

Resolution and preset modes

- Max. resolution 1280 x 960
 - Recom. resolution 800 x 600
 - 16 user definable modes
 - 18 factory preset modes:
- | | H.freq (kHz)/V.freq (Hz) |
|------------|---|
| 640 x 350 | 31.5K/70; 37.9K/85 |
| 640 x 480 | 31.5K/60; 37.9K/72; 37.5K/75; 43.3K/85; 50.6K/100 |
| 720 x 400 | 31.5K/70; 37.9K/85 |
| 800 x 600 | 37.9K/60; 48.1K/72; 46.9K/75; 53.7K/85 |
| 832 x 624 | 49.7K/75 |
| 1024 x 768 | 48.4K/60; 56.5K/70; 60.0K/75 |
| 1280 x 960 | 60.0K/60 |

Plug and play compatibility

- Display Data Channel DDC 1/2B
- Microsoft® Windows® 95/98/NT/2000 compatible

Power management

Complies with EPA Energy Star and NUTEK specifications

- Operation (typ.) 65 W
- Suspend/Stand By mode (typ.) < 10 W
- Off mode/ Deep Sleep < 8 W

Low-emission characteristics

- Complies with MPR-II specifications

Monitor controls and functions

- Main 5-button OSD
Brightness +/- direct access
Contrast +/- direct access
- On Screen Display Language (English, Spanish, French, German, Italian), zoom, horizontal, vertical, pincushion, balanced, trapezoid, parallelogram, color, reset, moire, serial, number, resolution, frequency

Connections and Cables

- Connections -Video 15-pin D-Shell
- Cables Video(fixed) and Power

Regulatory approvals

- MPR-II Low Emission
- TÜV/GS, TÜV-Ergo, TÜV/9241-3
- FCC-B, UL, CSA, DHHHS
- SEMKO, Poland-B sign, C-Tick
- VCC-I, CE, BCIQ, PSB

Physical specifications

- Dim. incl. base (WxHxD)(mm) 358 x 370 x 379
- Dim. incl. base (WxHxD)(inch) 14.1" x 14.6" x 14.9"
- Dim. excl. base (WxHxD)(mm) 358 x 335 x 379
- Dim. excl. base (WxHxD)(inch) 14.1" x 13.2" x 14.9"
- Weight (kg) 12.2 kg
- Power supply 90 - 264 VAC, 50/60Hz
- Temperature (operational) 0°C to 40°C/ 32°F to 104°F
- Temperature (storage) -25°C to 65°C/ -13°F to 149°F
- Relative humidity 5% to 95%
- MTBF (excl. CRT) > 75,000 H

Other

- USB Hub option type: PCUH411
- Multimedia Base option type: 6G3B11

This monitor fulfills all Nutek requirements regarding power management. Philips is a partner in the EPA's Energy Star Computers Program. As an Energy Star partner, Philips has determined that this product meets the Energy Star guidelines for energy efficiency. MAC is a registered trademark of Apple Computer, Inc. MS-DOS is a registered trademark and Windows® 95/98/NT/2000 is a trademark of Microsoft Corp. All trademark acknowledged. Copyright © 2000 Philips Electronics N.V.

All data subject to change without notice
Release date: June 2000
www.philips.com

Let's make things better.



PHILIPS