

# Specifications

## MicroTouch™ M150 FPD Touch Monitor

15"

### FUNCTIONAL FEATURES

LCD Technology	TFT, Active Matrix
Display Colors	262,144
Pixel Pitch	.297 mm
Brightness w/o touch screen	250 cd/m <sup>2</sup> typical
Brightness with touch screen (max.) <sup>1</sup>	215 cd/m <sup>2</sup> typical
Contrast Ratio	300:1
Response Time	35 ms typical
Viewing Angle	Horizontal: +/-60 degrees typical Vertical: +40/-60 degrees typical
Front Panel Buttons	Menu, Select, Adjust, Power
On Screen Display Controls	Brightness, Contrast, Horizontal/Vertical Position, Clock, Phase, Auto Phase, Color,
Maximum Resolution	1024 x 768
Number of Allowable Unlit Pixels	10
Operating Environment	Operating Temperature: 0 to 40 degrees C 90% Relative Humidity, Non-condensing
Storage Environment	-25 to +60 degrees C

### PHYSICAL FEATURES

Physical Dimensions (WxHxD) (Depth includes base)	408 x 398.3 x 258.7 mm 16.1 x 15.7 x 10.2 inches
Display Area (WxH)	304.1 x 228.1 mm 12 x 9 inches
Video Cable Connector	15-pin D-sub
Power Supply	12V DC Power Supply
Power Savings <sup>2</sup>	DPMS, VESA Compliant
Power Consumption	<28W, Normal Operation
Backlight Life	50,000 hrs. typical
Weight (Net)	7.4 kg/16.3 lbs.
Agency Approvals	FCC B, CE, UL/cUL
Mounting Options	VESA mounting compatible
Multimedia	Equipped with speakers in base
Color Option	Available in Black
Warranty	30 Months FPD 5 Years Touch Sensor and Components



VESA Mounting Compatibility



Key hole pattern provides additional security.

(1) Brightness measured using MicroTouch capacitive C-etch sensor

(2) DPMS: Display power management signaling for reduced power consumption during non-use.

**Notice:** Given the variety of factors that can affect the use and performance of a 3M Touch Systems product, including that solid state equipment has operation characteristics different from electromechanical equipment, some of which factors are uniquely within User's knowledge and control, it is essential that User evaluate the 3M Touch Systems product to determine whether it is suitable for User's particular purpose and suitable for User's method of application. 3M Touch Systems' statements, engineering/technical information, and recommendations are provided for User's convenience, but their accuracy or completeness is not warranted. 3M Touch Systems products are not specifically designed for use in medical devices as defined by United States federal law. 3M Touch Systems products should not be used in such applications without 3M Touch Systems' express written consent. User should contact its sales representative if User's opportunity involves a medical device application.

**IMPORTANT NOTICE TO PURCHASER:** Specifications are subject to change without notice. 3M Touch Systems' Products are warranted to meet their published specifications from the date of shipment and for the period stated in the specification. **3M Touch Systems makes no additional warranties, express or implied, including but not limited to any implied warranties of merchantability or fitness for a particular purpose.** User is responsible for determining whether the 3M Touch Systems products are fit for User's particular purpose and suitable for its method of production, including intellectual property liability for User's application. If a Product is proven not to have met 3M Touch Systems' warranty, then 3M Touch Systems' sole obligation and User's and Purchaser's **exclusive remedy**, will be, at 3M Touch Systems' option, to repair or replace that Product quantity or to refund its purchase price. 3M Touch Systems has no obligation under 3M Touch Systems' warranty for any Product that has been modified or damaged through misuse, accident, neglect, or subsequent manufacturing operations or assemblies by anyone other than 3M Touch Systems. **3M Touch Systems shall not be liable in any action against it in any way related to the Products for any loss or damages, whether non-specified direct, indirect, special, incidental or consequential (including downtime, loss of profits or goodwill) regardless of the legal theory asserted.** (11/01R2)



3M Touch Systems UK Ltd.  
3M Optical Systems Division  
163 Milton Park  
Abindon  
Oxon OX14 4SD  
United Kingdom  
+44 (0) 1235-444400.

Worldwide Manufacturing Plants:  
Austin, Texas  
Methuen, Massachusetts  
Milwaukee, Wisconsin  
Vancouver, BC Canada  
Abingdon, UK

For more information on 3M touch products,  
visit [3Mtouch.com](http://3Mtouch.com) or call +44 (0) 1235-444400

[www.3Mtouch.com](http://www.3Mtouch.com)

MicroTouch is a trademark of 3M.

© 3M 2002  
M150FPD-0-04-02-EMEA

# MicroTouch



## MicroTouch™ M150 FPD Touch Monitor

TOUCH MONITORS



### *Product Highlights*

- Maximum touch stability
- Display angle adjustable from 0 to 60 degrees
- Positive locking adjustment feature
- VESA mounting compatible
- Cable management designed in
- Multimedia equipped

### **A new Benchmark in Flat Panel Touch Displays**

At 3M Touch Systems, we envisioned a touch monitor that would set a new standard of excellence. By combining our current and future touch technologies with a monitor form factor that is a breakthrough in display design, a new benchmark for touch displays has been created. This new design combines patent-pending features with the quality, accuracy and durability of 3M touch screen technology to create an innovative touch display solution. It's what you'd expect from a leader in innovation. It's what you'd expect from 3M.

### **Making the Difference**

At 3M Touch Systems, we know each touch monitor application has a unique set of requirements. That's why the MicroTouch M150 FPD monitor is offered with a choice of capacitive or resistive touch technology.

MicroTouch ClearTek capacitive touch technology provides accuracy and sensitivity to the user's touch while offering outstanding durability and resistance to contaminants such as dirt, liquids, and harsh chemicals. Our 5-wire resistive technology not only provides contaminant resistance, but is responsive to the touch of stylus as well as fingernails, credit cards, gloved hands and bare fingers.