

## Specifications

ML-1650/ML-1651N		
<b>Engine</b>	Speed	16 ppm(A4), 17 ppm(Letter)
	Resolution	1200dpi
	FPOT	Under 14 sec.
	Acoustic Noise	43dB
	Power Consumption	Under 20W (sleep mode)
	Dimension	362x409x293mm
<b>Controller</b>	Weight	11kg(with Toner)
	Processor	Power PC 603e 166MHz Processor
	Memory	SDRAM 16MB (up to 144MB)
	Emulation	PCL6 Emulation Compatible
		PostScript 3 Compatible(Optional)
	Interface	IEEE 1284, USB
<b>Driver</b>	Fonts	Windows® Fonts
	OS Support	Windows 95/98/2000/Me/NT, Linux/Red Hat 6.0/7, Mac OS 8/9/10
	Function	N-up, Overlay, Watermark, Poster
<b>Paper</b>	Input	550 CST + 100 MP
	Output	250 Face Down + 100 Face Up
	Manual	1 Sheet
	Media Type	A4, Letter, Legal, Executive, B5, A5, Folia, 7 3/4(Monarch) #10, DL, C5, C6, B5
	Media Weight	16-53lb
<b>User Interface</b>	Toner Cartridge	8,000 Pages @5% Coverage
	Toner Save	YES(button)
	Reprint/Cancel	YES(button)
	Options	Ethernet 10/100 Base Tx(ML-1651N Standard) 550 Pages Second Cassette Feeder PostScript Level 3 Emulation Compatible



Push & Save  
Push & Save

## Laser Printer for Small Workgroup



## Laser Printer for Small Workgroup ML-1650/ML-1651N

### ML-1650/ML-1651N

- 16ppm Printing Speed
- Power PC 603e 166MHz Processor
- 1200dpi Resolution
- 16MB Memory(SDRAM, up to 144MB)
- PCL6 Emulation Compatible
- Toner Save Button



<b>Consumable</b>	8,000 Pages Toner	ML-1650D8
<b>Option</b>	16MB SDRAM Memory	ML-00MA
	32MB SDRAM Memory	ML-00MB
	64MB SDRAM Memory	ML-00MC
	128MB SDRAM Memory	ML-00MD
	Second Cassette Feeder	ML-1650S6
	10/100 Base Tx Network Card	ML-00NA
	PostScript 3 Emulation Module	ML-00PA



\*Design & Specifications are subject to change without notice.

SAMSUNG

HEAD OFFICE(SEOUL, KOREA)

Samsung Main Bldg.

250, 2-Ka, Teopyeong-Ro Chung-Ku

Seoul, Korea 100-742

Tel:82-2-751-2114 Fax:82-2-751-2923

<http://www.samsungprinter.com>SAMSUNG DIGITall  
everyone's invited.SAMSUNG DIGITall  
everyone's invited.